

Methods

Object

toString
toLocaleString
valueOf
hasOwnProperty
isPrototypeOf
propertyIsEnumerable

String

charAt
charCodeAt
fromCharCode
concat
indexOf
lastIndexOf
localeCompare
match
replace
search
slice
split
substring
substr
toLowerCase
toUpperCase
toLocaleLowerCase
toLocaleUpperCase

RegExp

test
match
exec

Array

concat
join
push
pop
reverse
shift
slice
sort
splice
unshift

Number

toFixed
toExponential
toPrecision

Date

parse
toDate
toISOString
getTime
getDate
getDay
getFullYear
getHours
getMilliseconds
getMinutes
getMonth
getSeconds
getTime
getTimezoneOffset
getYear
setDate
setHours
setMilliseconds
setMinutes
setMonth
setSeconds
setYear
toLocaleTimeString

JavaScript

XMLHttpRequest

Safari, Mozilla, Opera:

```
var req = new XMLHttpRequest();
```

Internet Explorer:

```
var req = new  
ActiveXObject("Microsoft.XMLHTTP");
```

XMLHttpRequest Object Methods

```
abort()  
getAllResponseHeaders()  
getResponseHeader(header)  
open(method, URL)  
send(body)  
setRequestHeader(header, value)
```

XMLHttpRequest Object Properties

```
onreadystatechange  
readyState  
responseText  
responseXML  
status  
statusText
```

XMLHttpRequest readyState Values

0	Uninitiated
1	Loading
2	Loaded
3	Interactive
4	Complete

JAVASCRIPT IN HTML

External JavaScript File

```
<script type="text/javascript"  
src="javascript.js"></script>
```

Inline JavaScript

```
<script type="text/javascript">  
<!--  
    // JavaScript Here  
//-->  
</script>
```

Functions

Window

```
alert  
blur  
clearTimeout  
close  
focus  
open  
print  
setTimeout
```

Built In

```
eval  
parseInt  
parseFloat  
isNaN  
isFinite  
decodeURI  
decodeURIComponent  
encodeURIComponent  
encodeURIComponent  
escape  
unescape
```

REGULAR EXPRESSIONS - FORMAT

Regular expressions in JavaScript take the form:

```
var RegEx = /pattern/modifiers;
```

REGULAR EXPRESSIONS - MODIFIERS

/g	Global matching
/i	Case insensitive
/s	Single line mode
/m	Multi line mode

REGULAR EXPRESSIONS - PATTERNS

^	Start of string
\$	End of string
.	Any single character
(a b)	a or b
(...)	Group section
[abc]	Item in range (a or b or c)
[^abc]	Not in range (not a or b or c)
a?	Zero or one of a
a*	Zero or more of a
a+	One or more of a
a{3}	Exactly 3 of a
a{3,}	3 or more of a
a{3,6}	Between 3 and 6 of a
!(pattern)	"Not" prefix. Apply rule when URL does not match pattern.

EVENT HANDLERS

onAbort	onMouseDown
onBlur	onMouseMove
onChange	onMouseOut
onClick	onMouseOver
onDbClick	onMouseUp
onDragDrop	onMove
onError	onReset
onFocus	onResize
onKeyDown	onSelect
onKeyPress	onSubmit
onKeyUp	onUnload
onLoad	

FUNCTIONS AND METHODS

A method is a type of function, associated with an object. A normal function is not associated with an object.

Available free from
AddedBytes.com

DOM Methods

Document

```
clear  
createDocument  
createDocumentFragment  
createElement  
createEvent  
createEventObject  
createRange  
createTextNode  
getElementsByTagName  
getElementById  
write
```

Node

```
addEventListener  
appendChild  
attachEvent  
cloneNode  
createTextRange  
detachEvent  
dispatchEvent  
fireEvent  
getAttributeNS  
getAttributeNode  
hasChildNodes  
hasAttribute  
hasAttributes  
insertBefore  
removeChild  
removeEventListener  
replaceChild  
scrollIntoView
```

Form

```
submit
```

DOM Collections

```
item
```

Range

```
collapse  
createContextualFragment  
moveEnd  
moveStart  
parentElement  
select  
setStartBefore
```

Style

```
getPropertyValue  
setProperty
```

Event

```
initEvent  
preventDefault  
stopPropagation
```

XMLSerializer

```
serializeToString
```

XMLHTTP

```
open  
send
```

XMLDOM

```
loadXML
```

DOMParser

```
parseFromString
```